

2012 - Mazda6 - Engine

DTC P061F:00 [MZR 2.5]

DTC P061F:00	Internal control module throttle valve actuator controller performance problem
DETECTION CONDITION	- Indicates that a calculation error occurred in the PCM. Diagnostic support note - This is a continuous monitor (other). - The MIL does not illuminate. - FREEZE FRAME DATA (Mode2)/Snapshot data is not available. - The DTC is stored in PCM memory.
POSSIBLE CAUSE	NOTE: - This DTC is an informational DTC and may be set in combination with a number of other DTCs which are causing the FMEM. Diagnose other DTCs first. - PCM connector or terminal malfunction - PCM malfunction

Diagnostic procedure

STEP	INSPECTION	ACTION
1	VERIFY RELATED REPAIR INFORMATION AVAILABILITY	Yes Perform repair or diagnosis according to the available repair information.
	- Verify related Service Bulletins and/or on-line repair information availability. - Is any related repair information available?	No Go to the next step.
2	VERIFY RELATED PENDING AND STORED DTC	Yes Go to the applicable DTC inspection. (See DTC TABLE [MZR 2.5] .)
	Switch the ignition to off, then to ON (engine off).	No Go to the next step.

	Verify pending and stored DTCs using the M-MDS. (See ON-BOARD DIAGNOSTIC TEST [MZR 2.5].) Are any other DTCs present?		
3	INSPECT PCM CONNECTOR CONDITION - Switch the ignition to off. - Disconnect the PCM connector. - Inspect for poor connection (such as damaged/pulled-out pins, corrosion). - Is there any malfunction?	Yes	Repair or replace the terminal and/or connector, then go to the next step.
		No	Connect the PCM connector and verify that the connector seat correctly, then go to the next step.
4	VERIFY DTC TROUBLESHOOTING COMPLETED - Make sure to reconnect all disconnected connectors. - Clear the DTC from the PCM memory using the M-MDS. (See AFTER REPAIR PROCEDURE [MZR 2.5].) - Perform the KOEO or KOER self test. (See KOEO/ KOER SELF TEST [MZR 2.5].) - Is the same DTC present?	Yes	Replace the PCM, then go to the next step. (See PCM REMOVAL/ INSTALLATION [MZR 2.5] .)
		No	Go to the next step.
5	VERIFY AFTER REPAIR PROCEDURE - Perform the "AFTER REPAIR PROCEDURE". (See AFTER REPAIR PROCEDURE [MZR 2.5].) - Are any DTCs present?	Yes	Go to the applicable DTC inspection. (See DTC TABLE [MZR 2.5] .)
		No	DTC troubleshooting completed.

2012 - Mazda6 - Engine

DTC P061F:00 [MZR 2.5]

DTC P061F:00	Internal control module throttle valve actuator controller performance problem
DETECTION CONDITION	- Indicates that a calculation error occurred in the PCM. Diagnostic support note - This is a continuous monitor (other). - The MIL does not illuminate. - FREEZE FRAME DATA (Mode2)/Snapshot data is not available. - The DTC is stored in PCM memory.
POSSIBLE CAUSE	NOTE: - This DTC is an informational DTC and may be set in combination with a number of other DTCs which are causing the FMEM. Diagnose other DTCs first. - PCM connector or terminal malfunction - PCM malfunction

Diagnostic procedure

STEP	INSPECTION	ACTION
1	VERIFY RELATED REPAIR INFORMATION AVAILABILITY Verify related Service Bulletins and/or on-line repair information availability.	Yes Perform repair or diagnosis according to the available repair information. If the vehicle is not repaired, go to the next step.
	Is any related repair information available?	No Go to the next step.
2	VERIFY RELATED PENDING AND STORED DTC Switch the ignition to off, then to ON (engine off).	Yes Go to the applicable DTC inspection. (See DTC TABLE [MZR 2.5] .)
		No Go to the next step.

	Verify pending and stored DTCs using the M-MDS. (See ON-BOARD DIAGNOSTIC TEST [MZR 2.5].) Are any other DTCs present?		
3	INSPECT PCM CONNECTOR CONDITION - Switch the ignition to off. - Disconnect the PCM connector. - Inspect for poor connection (such as damaged/pulled-out pins, corrosion). - Is there any malfunction?	Yes	Repair or replace the terminal and/or connector, then go to the next step.
		No	Connect the PCM connector and verify that the connector seat correctly, then go to the next step.
4	VERIFY DTC TROUBLESHOOTING COMPLETED - Make sure to reconnect all disconnected connectors. - Clear the DTC from the PCM memory using the M-MDS. (See AFTER REPAIR PROCEDURE [MZR 2.5].) - Perform the KOEO or KOER self test. (See KOEO/ KOER SELF TEST [MZR 2.5].) - Is the same DTC present?	Yes	Replace the PCM, then go to the next step. (See PCM REMOVAL/ INSTALLATION [MZR 2.5] .)
		No	Go to the next step.
5	VERIFY AFTER REPAIR PROCEDURE - Perform the "AFTER REPAIR PROCEDURE". (See AFTER REPAIR PROCEDURE [MZR 2.5].) - Are any DTCs present?	Yes	Go to the applicable DTC inspection. (See DTC TABLE [MZR 2.5] .)
		No	DTC troubleshooting completed.