

2012 - Mazda6 - Engine

DTC P1674:00 [MZR 2.5]

DTC P1674:00	Control module software corrupted
DETECTION CONDITION	- Indicates that an error occurred in the PCM. This DTC is set in combination with P2105:00. Diagnostic support note - This is a continuous monitor (CCM). - The MIL illuminates if the PCM detects the above malfunction condition during the first drive cycle. - FREEZE FRAME DATA (Mode 2)/Snapshot data is available. - The DTC is stored in the PCM memory.
POSSIBLE CAUSE	- PCM malfunction - Software incompatibility issue

Diagnostic procedure

STEP	INSPECTION		ACTION
1	VERIFY FREEZE FRAME DATA (MODE 2)/ SNAPSHOT DATA HAS BEEN RECORDED	Yes	Go to the next step.
	Has the FREEZE FRAME DATA (Mode 2)/snapshot data been recorded?	No	Record the FREEZE FRAME DATA (Mode 2)/snapshot data on the repair order, then go to the next step.
2	VERIFY RELATED REPAIR INFORMATION AVAILABILITY	Yes	Perform repair or diagnosis according to the available repair information. If the vehicle is not repaired, go to the next step.
	- Verify related Service Bulletins and/or on-line repair information availability. - Is any related repair information available?	No	Go to the next step.
3	VERIFY DTC TROUBLESHOOTING COMPLETED	Yes	Replace the PCM, then go to the next step.

	• Clear the DTC from the PCM memory using the M-MDS. (See AFTER REPAIR PROCEDURE [MZR 2.5].) • Perform the KOEO or KOER self test. (See KOEO/ KOER SELF TEST [MZR 2.5].) • Is the same DTC present?		(See PCM REMOVAL/ INSTALLATION [MZR 2.5] .)
		No	Go to the next step.
4	VERIFY AFTER REPAIR PROCEDURE • Perform the "AFTER REPAIR PROCEDURE". (See AFTER REPAIR PROCEDURE [MZR 2.5].) • Are any DTCs present?	Yes	Go to the applicable DTC inspection. (See DTC TABLE [MZR 2.5] .)
		No	DTC troubleshooting completed.

2012 - Mazda6 - Engine

DTC P1674:00 [MZR 2.5]

DTC P1674:00	Control module software corrupted
DETECTION CONDITION	- Indicates that an error occurred in the PCM. This DTC is set in combination with P2105:00. Diagnostic support note - This is a continuous monitor (CCM). - The MIL illuminates if the PCM detects the above malfunction condition during the first drive cycle. - FREEZE FRAME DATA (Mode 2)/Snapshot data is available. - The DTC is stored in the PCM memory.
POSSIBLE CAUSE	- PCM malfunction - Software incompatibility issue

Diagnostic procedure

STEP	INSPECTION		ACTION
1	VERIFY FREEZE FRAME DATA (MODE 2)/ SNAPSHOT DATA HAS BEEN RECORDED	Yes	Go to the next step.
	Has the FREEZE FRAME DATA (Mode 2)/snapshot data been recorded?	No	Record the FREEZE FRAME DATA (Mode 2)/snapshot data on the repair order, then go to the next step.
2	VERIFY RELATED REPAIR INFORMATION AVAILABILITY	Yes	Perform repair or diagnosis according to the available repair information. If the vehicle is not repaired, go to the next step.
	- Verify related Service Bulletins and/or on-line repair information availability. - Is any related repair information available?	No	Go to the next step.
3	VERIFY DTC TROUBLESHOOTING COMPLETED	Yes	Replace the PCM, then go to the next step.

	• Clear the DTC from the PCM memory using the M-MDS. (See AFTER REPAIR PROCEDURE [MZR 2.5].) • Perform the KOEO or KOER self test. (See KOEO/ KOER SELF TEST [MZR 2.5].) • Is the same DTC present?		(See PCM REMOVAL/ INSTALLATION [MZR 2.5] .)
		No	Go to the next step.
4	VERIFY AFTER REPAIR PROCEDURE • Perform the "AFTER REPAIR PROCEDURE". (See AFTER REPAIR PROCEDURE [MZR 2.5].) • Are any DTCs present?	Yes	Go to the applicable DTC inspection. (See DTC TABLE [MZR 2.5] .)
		No	DTC troubleshooting completed.