

2012 - Mazda6 - Suspension

WHEEL AND TIRE SPECIFICATION [General (L.H.D.) specs.]

Standard tire and wheel

Item			Specification	
Wheel	Size		17 x 7J	18 x 8J
	Inset	(mm {in})	55 {2.17}	60 {2.4}
	Pitch circle diameter	(mm {in})	114.3 {4.50}	
	Material		Aluminum alloy	
Tire	Size		P215/55R17 93V	P235/45R18 94W
	Air pressure (kPa {(bar), <psi>})	Front	220 {(2.2), <32>}	
		Rear	220 {(2.2), <32>}	
	Remaining tread	(mm {in})	1.6 {0.063} min.	
Wheel and tire	Lug nut tightening torque(N·m {kgf·m, ft·lbf})		88—118 {9.0—12, 65—87}	
	Wheel and tire runout	Radial direction	1.5 {0.059} max.	
		(mm {in})Lateral direction	2.0 {0.078} max.	
	Wheel imbalance	(g {oz})	Adhesive-type*1: 14 {0.49} max. Knock-type*2: 9 {0.3} max.	Adhesive-type*1: 13 {0.46} max. Knock-type*2: 8 {0.28} max.

Spare tire and wheel

Item	Specification

Wheel	Size		16 x 6 1/2J
	Inset	(mm {in})	55 {2.17}
	Pitch circle diameter	(mm {in})	114.3 {4.50}
	Material		Steel
Tire	Size		205/60R16 92H
	Air pressure (kPa {(bar), <psi>})	Front	240 {(2.4), <35>}
		Rear	
	Remaining tread	(mm {in})	1.6 {0.063} min.
Wheel and tire	Lug nut tightening torque	(N·m {kgf·m, ft·lbf})	88—118 {9.0—12, 65—87}

*1
Total weight exceeds 160 g { 5.65 oz} .

*2
One balance weight: 60 g { 2.12 oz} max. If the total weight exceeds 100 g { 3.53 oz} on one side, rebalance after moving the tire around on the rim. Do not use three or more balance weights.

[< Previous](#) [Next >](#)

[Back to Top](#)

2012 - Mazda6 - Suspension

WHEEL AND TIRE SPECIFICATION [General (L.H.D.) specs.]

Standard tire and wheel

Item			Specification	
Wheel	Size		17 x 7J	18 x 8J
	Inset	(mm {in})	55 {2.17}	60 {2.4}
	Pitch circle diameter	(mm {in})	114.3 {4.50}	
	Material		Aluminum alloy	
Tire	Size		P215/55R17 93V	P235/45R18 94W
	Air pressure (kPa {(bar), <psi>})	Front	220 {(2.2), <32>}	
		Rear	220 {(2.2), <32>}	
	Remaining tread	(mm {in})	1.6 {0.063} min.	
Wheel and tire	Lug nut tightening torque(N·m {kgf·m, ft·lbf})		88—118 {9.0—12, 65—87}	
	Wheel and tire runout	Radial direction	1.5 {0.059} max.	
		(mm {in})Lateral direction	2.0 {0.078} max.	
	Wheel imbalance	(g {oz})	Adhesive-type*1: 14 {0.49} max. Knock-type*2: 9 {0.3} max.	Adhesive-type*1: 13 {0.46} max. Knock-type*2: 8 {0.28} max.

Spare tire and wheel

Item	Specification

Wheel	Size		16 x 6 1/2J
	Inset	(mm {in})	55 {2.17}
	Pitch circle diameter	(mm {in})	114.3 {4.50}
	Material		Steel
Tire	Size		205/60R16 92H
	Air pressure (kPa {(bar), <psi>})	Front	240 {(2.4), <35>}
		Rear	
	Remaining tread	(mm {in})	1.6 {0.063} min.
Wheel and tire	Lug nut tightening torque	(N·m {kgf·m, ft·lbf})	88—118 {9.0—12, 65—87}

*1
Total weight exceeds 160 g { 5.65 oz} .

*2
One balance weight: 60 g { 2.12 oz} max. If the total weight exceeds 100 g { 3.53 oz} on one side, rebalance after moving the tire around on the rim. Do not use three or more balance weights.

[< Previous](#) [Next >](#)

[Back to Top](#)