

2012 - Mazda6 - DriveLine/ Axle

DRIVE LINE/ AXLE TECHNICAL DATA

Item		Specification
Maximum front wheel bearing play		0.05 mm {0.002 in}
Maximum rear wheel bearing play		0.05 mm {0.002 in}
Drive shaft standard length [ATX (Tripod joint)]	MZR 2.5	LH: 703.2—713.2 mm {27.69—28.07 in} RH: 659.3—669.3 mm {25.96—26.35 in}
	MZI 3.7 V6	LH: 636.2—646.2 mm {25.05—25.44 in} RH: 608.2—618.2 mm {23.95—24.33 in}
Drive shaft standard length [MTX (Double offset joint)]		LH: 705.6—715.6 mm {27.78—28.17 in} RH: 656—666 mm {25.9—26.2 in}

2012 - Mazda6 - DriveLine/ Axle

DRIVE LINE/ AXLE TECHNICAL DATA

Item		Specification
Maximum front wheel bearing play		0.05 mm {0.002 in}
Maximum rear wheel bearing play		0.05 mm {0.002 in}
Drive shaft standard length [ATX (Tripod joint)]	MZR 2.5	LH: 703.2—713.2 mm {27.69—28.07 in} RH: 659.3—669.3 mm {25.96—26.35 in}
	MZI 3.7 V6	LH: 636.2—646.2 mm {25.05—25.44 in} RH: 608.2—618.2 mm {23.95—24.33 in}
Drive shaft standard length [MTX (Double offset joint)]		LH: 705.6—715.6 mm {27.78—28.17 in} RH: 656—666 mm {25.9—26.2 in}